



BALLOONS

1.	Mechanical Watertight Connection Seal
2.	Drain Body
3.	Aluminum Clamping Ring
4.	Metal Stud with Self Locking Nut
5.	Aluminum Strainer Dome
6.	Sealant
7.	Torched or Mopped Asphalt Bond
8.	Reinforcing Ply
9.	Existing Rain Water Leader
10.	Existing Cast Iron Drain Bowl
11.	Substrate
12.	Vapor Retarder (optional)
13.	Treated Wood Nailer (optional)
14.	Insulation (sloped to drain)
15.	Flange Fastener
16.	Wood Nailer Fastener
17.	Cap Sheet
18.	Base Sheet

APPLICATIONS

MODIFIED BITUMEN-APP/SBS

SIZES:

3 INCH, 4 INCH, 5 INCH, 6 INCH

NOTES:

1-REFER TO ROOF MEMBRANE MANUFACTURER FOR THEIR APPROVED INSTALLATION DETAIL.

2-HERCULES RETRODRAIN COMPLIES WITH ANSI/SPRI RD-1.



OMG Inc.
 153 Bowles Road
 Agawam, MA 01001
800-633-3800
 info@olyfast.com
 www.olyfast.com

NAME:		HERCULES RETRODRAIN		
DRWN. BY: JLM	DATE: 8/08/2011	SKU:	HDAL_A (INSERT SIZE)	
APPD. BY: DG	DATE: 8/08/2011	SCALE:	NOT TO SCALE	SHEET: 1 OF 1